

Laser cutting recommendation Eurolaser *

Grade	Thickness	V (mm/sec)	L-Power watts	L-Power in %	compressed air (bar)	Lens	Noozle (mm)	Frequenzy (Hz)
KROMA Displayboard	1.0 mm	300	200	100	5	5,0"	2	20.000
KROMA Displayboard	2.0 mm	150	200	100	4	5,0"	2	20.000
KROMA Displayboard	3.8 mm	100	200	100	4	5,0"	2	20.000
KROMA Displayboard	5.0 mm	70	200	100	5	5,0"	2	20.000
KROMA Natural White	1.0 mm	300	200	100	5	5,0"	2	20.000
KROMA Natural White	2.0 mm	180	200	100	5	5,0"	2	20.000
KROMA Natural White	3.0 mm	125	200	100	5	5,0"	2	20.000
KROMA Kraft	1.0 mm	300	200	100	5	5,0"	2	20.000
KROMA Kraft	2.0 mm	150	200	100	5	5,0"	2	20.000
KROMA Kraft	3.0 mm	125	200	100	5	5,0"	2	20.000
KROMA Outdoor	1.1 mm	300	200	100	5	5,0"	2	20.000
KROMA Outdoor	1.5 mm	140	200	35	5	5,0"	2	20.000
Studioboard	0.7 mm	500	200	100	5	5,0"	2	20.000
Studioboard	0.9 mm	300	200	100	5	5,0"	2	20.000
KROMA All Black	1.8 mm	150	200	100	4	5,0"	2	20.000
KROMA All Black	2.5 mm	100	200	100	4	5,0"	2	20.000
KROMA All Black	3.0 mm	70	200	100	4	5,0"	2	20.000
KROMA All White	1.0 mm	160	200	100	5	5,0"	2	20.000
KROMA All White	1.5 mm	140	200	100	5	5,0"	2	20.000
KROMA All White	2.0 mm	120	200	100	5	5,0"	2	20.000
KROMA All White	2.5 mm	100	200	100	5	5,0"	2	20.000
KROMA All White	3.0 mm	90	200	100	5	5,0"	2	20.000
Coaster Board	1.4 mm	100	200	20	4	5,0"	2	20.000
KROMA Inkjet Pro Matt	0.5 mm	50	200	10	3	3,75"	2	20.000
KROMA Inkjet Pro Matt	1.0 mm	50	200	9,5	3	3,75"	2	20.000
KROMA Inkjet Pro Matt	1.5 mm	50	200	14	3	3,75"	2	20.000
KROMA Inkjet Pro Matt	2.0 mm	50	200	17	3	3,75"	2	20.000
KROMA Inkjet Pro Matt	2.5 mm	50	200	21	3	3,75"	2	20.000

* EUROLASER M-800 STA / 400 watts. These are guidelines, however, there can be many different setting combinations